

Three Phase Hybrid Inverter

SUN- 6 / 8 / 10 / 12 K-SG04LP3-EL



48 48V low voltage battery, transformer isolation design

6 6 time periods for battery charging/discharging

240 Max. charging/discharging current of 240A

100% 100% unbalanced output, each phase
Max. output up to **50%** rated power

16 Frequency droop control, Max.10pcs parallel

DC couple and AC couple to retrofit existing solar system

Support storing energy from diesel generator

Model	SUN-6K-SG04LP3 -EU	SUN-8K-SG04LP3 -EU	SUN-10K-SG04LP3 -EU	SUN-12K-SG04LP3 -EU
Battery Input Data				
Battery Type	Lead-acid or Li-Ion			
Battery Voltage Range (V)	40~60			
Max. Charging Current (A)	150	190	210	240
Max. Discharging Current (A)	150	190	210	240
Charging Curve	3 Stages / Equalization			
External Temperature Sensor	Yes			
Charging Strategy for Li-Ion Battery	Self-adaption to BMS			
PV String Input Data				
Max. DC Input Power (W)	7800	10400	13000	15600
PV Input Voltage (V)	550 (150~800)			
MPPT Range (V)	200-650			
Start-up Voltage (V)	160			
PV Input Current (A)	13+13	13+13	26+13	26+13
Max. PV ISC (A)	17+17	17+17	34+17	34+17
No. of MPPT Trackers	2			
No. of Strings Per MPPT Tracker	1+1	1+1	2+1	2+1
AC Output Data				
Rated AC Output and UPS Power (W)	6000	8000	10000	12000
Max. AC Output Power (W)	6600	8800	11000	13200
Peak Power (off grid)	2 times of rated power, 10 S			
AC Output Rated Current (A)	9	12	15	18
Max. AC Current (A)	13.5	18	23	27
Max. Continuous AC Passthrough (A)	50			
Output Frequency and Voltage	50/60Hz; 230/400Vac (Three phase)			
Grid Type	Three Phase			
Current Harmonic Distortion	THD<3% (Linear load<1.5%)			
Efficiency				
Max. Efficiency	97.60%			
Euro Efficiency	97.00%			
MPPT Efficiency	99.90%			
Protection				
PV Input Lightning Protection	Integrated			
Anti-islanding Protection	Integrated			
PV String Input Reverse Polarity Protection	Integrated			
Insulation Resistor Detection	Integrated			
Residual Current Monitoring Unit	Integrated			
Output Over Current Protection	Integrated			
Output Shorted Protection	Integrated			
Output Over Voltage Protection	Integrated			
Surge protection	DC Type II / AC Type II			
Certifications and Standards				
Grid Regulation	IEC61727, IEC62116, IEC60068, IEC61683, NRS 097-2-1			
Safety EMC / Standard	IEC62109-1/-2, IEC61000-6-1, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12			
General Data				
Operating Temperature Range (°C)	-25~60°C, >45°C Derating			
Cooling	Smart cooling			
Noise (dB)	<45 dB			
Communication with BMS	RS485; CAN			
Weight (kg)	34.5			
Size (mm)	422W×658H×281D			
Protection Degree	IP65			
Installation Style	Wall-mounted			
Warranty	5 years			